



## FEATURES

- Available in various mounting bases (100, 150, MB).
- Available in ground spreader or mid-level spreader versions.
- One stage alloy rotary lock leg extension for heavy duty clamping.
- Heavy duty all black anodised alloy tubing.
- Robust glass-filled polymer brackets.
- Integrated stainless steel foot spikes.
- Integrated transport clips to pack system down securely.
- 3 year warranty.

\*Pictured with #993 Mid-Level Spreader and #478 Feet (opt.)

\*\*Pictured with #2130 HDC Ground Spreader (opt.)

## HD Cine Tripods with Rotary Locking

### SPECIFICATIONS

Weight: 5.4 kg (11.9 lbs) - 100mm  
 5.6 kg (12.4 lbs) - 150mm  
 5.9 kg (13.2 lbs) - MB

#### Ground spreader version

Height range: 710-1539mm (28.0-60.6") - 100mm  
 727-1539mm (28.2-60.6") - 150mm  
 737-1549mm (29.0-61.0") - MB

#### Mid-level spreader version

Height range: 770-1537mm (30.3-60.1") - 100mm  
 790-1540mm (31.1-60.6") - 150mm  
 800-1550mm (31.5-61.0") - MB

### OPTIONAL ACCESSORIES

993 Mid-Level Spreader  
 478 Feet (set of 3)  
 2130 HDC Ground Spreader



#### AUSTRALIA

Miller Camera Support Equipment  
 30 Hotham Parade  
 Artarmon, Sydney, NSW 2064  
 Australia

Quality ISO 9001 P +61 2 9439 6377 F +61 2 9438 2819  
 sales@miller.com.au

#### EUROPE

Miller Fluid Heads (Europe) Ltd.  
 Unit 12A, Shepperton Business Park  
 Govett Avenue, Shepperton  
 Middlesex, TW17 8BA  
 United Kingdom

P +44 (0) 1932 222 888 F +44 (0) 1932 222 211  
 sales@millertripods-europe.com

#### USA

Miller Camera Support LLC  
 216 Little Falls Road (Unit 15 & 16),  
 Cedar Grove, New Jersey 07009  
 USA

P +1 (973) 857 8300 F +1 (973) 857 8188  
 sales@millertripods.us

## HDC TRIPOD SPECIFICATIONS

#	2109	2110	2111	2114	2115	2116	2120	2121	2122
Bowl	MB			150mm			100mm		
Height	Short	Std	Tall	Short	Std	Tall	Short	Std	Tall
Height range	365-910mm (14.4-35.8")	800-1550mm (31.5-61.0")	925-1775mm (36.4-70.0")	355-900mm (14.0-35.0")	790-1540mm (31.1-60.6")	915-1765mm (46.0-69.5")	315-895mm (12.4-35.2")	770-1537mm (30.3-60.1")	890-1755mm (35.0-69.1")
Travel length	610mm (24.0")	916mm (36.1")	1010mm (39.8")	600mm (23.6")	906mm (35.7")	1000mm (39.4")	600mm (23.6")	906mm (35.7")	1000mm (39.4")
Weight	4.8kg (10.6lbs)	5.9kg (13.2lbs)	6.4kg (14.1lbs)	4.5kg (9.9lbs)	5.6kg (12.4lbs)	6.2kg (13.7lbs)	4.3kg (9.5lbs)	5.4kg (11.9lbs)	6.0kg (13.2lbs)
Spreader (opt.)	993 + 478	993 + 478	993 + 478	993 + 478	993 + 478	993 + 478	993 + 478	993 + 478	993 + 478
#	2109G	2110G	2111G	2114G	2115G	2116G	2120G	2121G	2122G
Bowl	MB			150mm			100mm		
Height	Short	Std	Tall	Short	Std	Tall	Short	Std	Tall
Height range	415-900mm (16.4-35.4")	737-1549mm (29.0-61.0")	886-1764mm (34.9-69.5")	405-890mm (16.0-35.0")	727-1539mm (28.2-60.6")	876-1754mm (34.5-69.1")	370-900mm (14.6-35.4")	710-1539mm (28.0-60.6")	845-1690mm (33.3-66.5")
Travel length	640mm (25.2")	946mm (37.2")	1040mm (41.0")	630mm (24.8")	936mm (36.9")	1030mm (40.6")	630mm (24.8")	936mm (36.9")	1030mm (40.6")
Weight	4.8kg (10.6lbs)	5.9kg (13.2lbs)	6.4kg (14.1lbs)	4.5kg (9.9lbs)	5.6kg (12.4lbs)	6.2kg (13.7lbs)	4.3kg (9.5lbs)	5.4kg (11.9lbs)	6.0kg (13.2lbs)
Spreader (opt.)	2132	2130	2130	2132	2130	2130	2132	2130	2130

**AUSTRALIA**  
 Miller Camera Support Equipment  
 30 Hotham Parade  
 Artarmon, Sydney, NSW 2064  
 Australia  
 Quality ISO 9001  
 P +61 2 9439 6377 F +61 2 9438 2819  
 sales@miller.com.au

**EUROPE**  
 Miller Fluid Heads (Europe) Ltd.  
 Unit 12A, Shepperton Business Park  
 Govett Avenue, Shepperton  
 Middlesex, TW17 8BA  
 United Kingdom  
 P +44 (0) 1932 222 888 F +44 (0) 1932 222 211  
 sales@millertripods-europe.com

**USA**  
 Miller Camera Support LLC  
 216 Little Falls Road (Unit 15 & 16),  
 Cedar Grove, New Jersey 07009  
 USA  
 P +1 (973) 857 8300 F +1 (973) 857 8188  
 sales@millertripods.us